



## LSTA-2200/LSTB-2200

门窗组装流水线 Windows and Doors System Assembly Production Line

### [性能特点]

适用于系统门窗流水线形式的高效组装。从涂抹组角胶、穿入角码及钢片开始，到组角、中挺拼装、安装胶条、安装五金、压条配做，直至包装完成，全部的生产作业均可在此流水线上完成。节省了人工搬运作业，可根据各个工序的实际用时，进行节拍优化，并可依据窗型及组装人员熟练程度进行变频调速。有效提高生产效率达40%以上。

### [Product Features]

It applies to system windows and doors efficient assembly. From applying corner glue, inserting corner kevs and steel plates, to corner connecting, install adhesive tape and hardware, until complete packing. All production operations can be done on this line. Save man power and time. It also can be adjusted speed according to practical application and worker proficiency. Effectively improve the production efficiency more than 40%.



### 技术参数 Technical Parameters

电源	Power supply	380V 50Hz
气源工作压力	Air consumption pressure	0.5-0.8Mpa
可加工窗型、窗扇长度、宽度	Processable window type, length / width	3000 / 2200mm
工作面高度	Worktable height	1200 / 1400mm
调速范围	Speed control range	0.5-1.5m/min
电机功率	Motor power	0.55kW